

Printing date 03.01.2012

Vers.No.: 5

Revision: 03.01.2012

1 Identification of the substance/mixture and of the company/undertaking					
· Product identifier					
· Trade name: SILIKAL RU 727					
 Article number: RU 727 Relevant identified uses of the substance or mixture and uses advised against Application of the substance / the preparation: Reaction resin Polyurethane resin 					
 Details of the supplier of the safety data sheet Manufacturer/Supplier: Silikal GmbH Ostring 23 D-63533 Mainhausen Tel.: +49-6182/9235-0 Fax.: +49-6182/9235-40 e-mail: mail@silikal.de 					
 Further information obtainable from: Environmental department Emergency telephone number: +49 6182 / 9235-0 					
2 Hazards identification					
· Classification of the substance or mixture					
· Classification according to Directive 67/548/EEC or Directive 1999/45/EC					
Xn; Harmful					
R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.					
Xi; Irritant					
R37/38: Irritating to respiratory system and skin.					
Xi; Sensitising					
R43: May cause sensitisation by skin contact.					
F; Highly flammable					
R11: Highly flammable.					
 R33: Danger of cumulative effects. Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. Classification system: The classification is according to the latest editions of the EU-lists, and extended by company and literature data. 					
· Label elements					
 Labelling according to EU guidelines: The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials. 					
· Code letter and hazard designation of product:					
Xn Harmful F Highly flammable					
Hazard-determining components of labelling:					
methyl methacrylate N,N-dimethyl-p-toluidine					
(Contd. on page 2)					

Printing date 03.01.2012

Vers.No.: 5

Revision: 03.01.2012

(Contd. of page 1)

Trade name: SILIKAL RU 727

		Ŀ				
•	Ris	K.	Dr	ıra	ses	52

11 Highly flammable.

20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

- 33 Danger of cumulative effects.
- 37/38 Irritating to respiratory system and skin.
- 43 May cause sensitisation by skin contact.

· Safety phrases:

- 3/7 Keep container tightly closed in a cool place.
- 9 Keep container in a well-ventilated place.
- 16 Keep away from sources of ignition No smoking.
- 23 Do not breathe fumes/aerosol.
- 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
- 60 This material and its container must be disposed of as hazardous waste.
- Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

Dangerous compor	ients.	
CAS: 80-62-6	methyl methacrylate	50-100%
EINECS: 201-297-1	🗙 Xi R37/38; 🗙 Xi R43; 👩 F R11	
CAS: 99-97-8	N,N-dimethyl-p-toluidine	0.5-2.5%
EINECS: 202-805-4	😡 T R23/24/25	
	R33-52/53	
Additional informat	tion: For the wording of the listed risk phrases refer to section 16	

Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air and to be sure call for a doctor.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

· Extinguishing media

• Suitable extinguishing agents:

- Foam
- Sand

CO2, sand, extinguishing powder. Do not use water.

· For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 3)

- GB

Printing date 03.01.2012

Vers.No.: 5

Revision: 03.01.2012

(Contd. of page 2)

Trade name: SILIKAL RU 727

Exothermic polymerization.
In case of fire, the following can be released:
Hydrocarbons
Carbon monoxide and carbon dioxide
· Advice for firefighters
 • Protective equipment: Wear self-contained respiratory protective device. • Additional information Cool endangered receptacles with water spray.
6 Accidental release measures
• Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Wear protective clothing.

· Special hazards arising from the substance or mixture

Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Environmental precautions: Do not allow to enter sewers/ surface or ground water.

 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

· Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

· Conditions for safe storage, including any incompatibilities

- · Storage:
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.

Store in cool, dry conditions in well sealed receptacles.

Do not allow to enter sewers/ surface or ground water.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Store receptacle in a well ventilated area. Protect from heat and direct sunlight.
- Maximum storage temperature: 25°C
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

GB

Printing date 03.01.2012

Colour:

· Odour threshold:

· Odour:

Vers.No.: 5

Revision: 03.01.2012

Trade name: SILIKAL RU 727

	(Contd. of page 3
· Control parameters	
Ingredients with limit values that require	monitoring at the workplace:
80-62-6 methyl methacrylate	
WEL Short-term value: 416 mg/m ³ , 100 pp Long-term value: 208 mg/m ³ , 50 ppm	
DNELS	
80-62-6 methyl methacrylate	
Dermal DNEL Dermal 17 mg/kg/d (-)	
Inhalative DNEL Inhalation 208 mg/m ³ (-)	
· Additional information: The lists valid duri	ng the making were used as basis.
· Exposure controls	
· Personal protective equipment:	
· General protective and hygienic measure	
Keep away from foodstuffs, beverages and	
Immediately remove all soiled and contamin Wash hands before breaks and at the end of	
Avoid contact with the skin.	i work.
Avoid contact with the eyes and skin.	
Respiratory protection:	
Self-contained respiratory protective device.	
Filter AX	se respiratory filter device. In case of intensive or longe
exposure use self-contained respiratory pro	
Protection of hands:	
M	
Protective gloves	
The glove material has to be impermeal	ble and resistant to the product/ the substance/ th
preparation.	
	ation of the penetration times, rates of diffusion and th
degradation · Material of gloves Nitrile rubber, NBR	
· Penetration time of glove material	
	nd out by the manufacturer of the protective gloves an
has to be observed.	
· Eye protection:	
Tightly sealed goggles	
Body protection: Protective work clothing	
Physical and chemical properties	
Information on basic physical and chemi	cal properties
General Information	
· Appearance:	
Form:	Fluid

Colourless

Unpleasant

Not determined.

(Contd. on page 5)

GB

Printing date 03.01.2012

Vers.No.: 5

Revision: 03.01.2012

Trade name: SILIKAL RU 727

	(Contd. of page 4)
· pH-value:	Not determined.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 100°C
· Flash point:	10°C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	430°C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
 Explosion limits: Lower: Upper: 	2.1 Vol % 12.5 Vol %
· Vapour pressure at 20°C:	38.7 hPa
 Density at 20°C: Relative density Vapour density Evaporation rate 	1 g/cm ³ Not determined. Not determined. Not determined.
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.
· Segregation coefficient (n-octanol/wate	r): Not determined.
 Viscosity: Dynamic at 20°C: Kinematic: Other information 	200 mPas Not determined. No further relevant information available.

10 Stability and reactivity

· Reactivity

· Chemical stability

• Thermal decomposition / conditions to be avoided:

Keep away from heat and direct sunlight.

No decomposition if used according to specifications.

- · Possibility of hazardous reactions Exothermic polymerization.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Reacts with peroxides and other radical forming substances.
- Hazardous decomposition products:

Hydrocarbons

Carbon monoxide and carbon dioxide

· Additional information: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 6)

GB

Printing date 03.01.2012

Γ

Vers.No.: 5

Revision: 03.01.2012

Trade name: SILIKAL RU 727

(Contd. of page 5)

	city:	vant for classification:
80-62-6 me		
	LD50	> 5000 mg/kg (rat)
	LD50	> 5000 mg/kg (kan)
		29.8 mg/l (rat)
		I-p-toluidine
	LC50	1650 mg/l (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50 (4h)	1.5 mg/l (rat)
· on the eye · Sensitizati	n: Irritant to : No irritati i on: Sensit	o skin and mucous membranes.
The produ	ct shows t	he following dangers according to the calculation method of the General E nes for Preparations as issued in the latest version:
12 Ecologia	alinfor	nation
12 Ecologic	ai miori	nation
· Toxicity		
· Aquatic to	xicity:	
Aquatic to 80-62-6 me	xicity: ethyl meth	acrylate
Aquatic to 80-62-6 me EC0	xicity: ethyl meth 100 mg/l	acrylate (Pseudomonas pudita)
Aquatic to 80-62-6 me EC0 EC3 (8d)	xicity: ethyl meth 100 mg/l 37 mg/l (acrylate (Pseudomonas pudita) Scenedesmus subspicatus od. quadricauda)
Aquatic to 80-62-6 me EC0 EC3 (8d) EC50 (48h	xicity: ethyl meth 100 mg/l 37 mg/l () 69 mg/l (acrylate (Pseudomonas pudita) Scenedesmus subspicatus od. quadricauda) Daphnia magna)
Aquatic to 80-62-6 me EC0 EC3 (8d) EC50 (48h EC50 (96h	xicity: ethyl meth 100 mg/l 37 mg/l () 69 mg/l () 170 mg/l	acrylate (Pseudomonas pudita) Scenedesmus subspicatus od. quadricauda) Daphnia magna) (Selenastrum capricornutum)
Aquatic to 80-62-6 me EC0 EC3 (8d) EC50 (48h EC50 (96h) LC50 (96h)	xicity: thyl meth 100 mg/l 37 mg/l () 69 mg/l () 170 mg/l) > 79 mg/	acrylate (Pseudomonas pudita) Scenedesmus subspicatus od. quadricauda) Daphnia magna) (Selenastrum capricornutum) 1 (fish)
Aquatic to 80-62-6 mo EC0 EC3 (8d) EC50 (48h EC50 (96h) LC50 (96h) NOEC	xicity: ethyl meth 37 mg/l (37 mg/l (69 mg/l (170 mg/l 79 mg/ 37 mg/l (acrylate (Pseudomonas pudita) Scenedesmus subspicatus od. quadricauda) Daphnia magna) (Selenastrum capricornutum) I (fish) Daphnia magna)
Aquatic to 80-62-6 me EC0 EC3 (8d) EC50 (48h EC50 (96h) LC50 (96h) NOEC 99-97-8 N,	xicity: ethyl meth 100 mg/l 37 mg/l () 69 mg/l () 170 mg/l) > 79 mg/ 37 mg/l (N-dimethy	acrylate (Pseudomonas pudita) Scenedesmus subspicatus od. quadricauda) Daphnia magna) (Selenastrum capricornutum) 1 (fish) Daphnia magna)
Aquatic to 80-62-6 me EC0 EC3 (8d) EC50 (48h EC50 (96h) LC50 (96h) NOEC 99-97-8 N, LC0 (96h)	xicity: thyl meth 100 mg/l 37 mg/l () 69 mg/l () 170 mg/l) > 79 mg/ 37 mg/l (N-dimethy 100 mg/l	acrylate (Pseudomonas pudita) Scenedesmus subspicatus od. quadricauda) Daphnia magna) (Selenastrum capricornutum) 1 (fish) Daphnia magna)

Printing date 03.01.2012

Vers.No.: 5

Revision: 03.01.2012

Trade name: SILIKAL RU 727

13 Disposal considerations

(Contd. of page 6)

· Waste treatment methods	
· Recommendation	
	ousehold garbage. Do not allow product to reach sewa
system.	ficial regulations
Must be specially treated adhering to of	ficial regulations.
· European waste catalogue	
07 02 08* other still bottoms and reaction	
15 01 10° packaging containing residue	es of or contaminated by dangerous substances
· Uncleaned packaging:	
Recommendation:	
Packaging may be reused or recycled a	
Disposal must be made according to of	re to be disposed of in the same manner as the product.
Recommended cleansing agents: Ac	
4 Transport information	
·UN-Number	
ADR, IMDG, IATA	UN1866
UN proper shipping name	
	1866 RESIN SOLUTION
	RESIN SOLUTION
• Transport hazard class(es)	
· Class · Label	3 Flammable liquids. 3
· IMDG, IATA	
	3 Flammable liquids.
· Label	3
 Packing group ADR, IMDG, IATA 	11
Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number:	F-E, <u>S-E</u>
· Transport in bulk according to Annex	
	۲ II of
MARPOL73/78 and the IBC Code	x II of Not applicable.

(Contd. on page 8)

Printing date 03.01.2012

Vers.No.: 5

Revision: 03.01.2012

(Contd. of page 7)

Trade name: SILIKAL RU 727

· Transport/Additional information:

· ADR

Tunnel restriction code

D/E

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



Xn Harmful F Highly flammable

 Hazard-determining components of labelling: methyl methacrylate N,N-dimethyl-p-toluidine

· Risk phrases:

- 11 Highly flammable.
- 20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
- 33 Danger of cumulative effects.
- 37/38 Irritating to respiratory system and skin.
- 43 May cause sensitisation by skin contact.

Safety phrases:

- 3/7 Keep container tightly closed in a cool place.
- 9 Keep container in a well-ventilated place.
- 16 Keep away from sources of ignition No smoking.
- 23 Do not breathe fumes/aerosol.
- 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
- 60 This material and its container must be disposed of as hazardous waste.
- · National regulations:

· Technical instructions (air):

Class	Share in %
II	50-100

• Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water. • Chemical safety assessment: A Chemical Safety Assessment has been carried out.

This info	mation is been an our present translades. However, this shall not constitute a super-	to c
	ormation is based on our present knowledge. However, this shall not constitute a guar	
for any s	pecific product features and shall not establish a legally valid contractual relationship.	
Bolovan	t phrases	
R11	Highly flammable.	
R23/24/2	25 Toxic by inhalation, in contact with skin and if swallowed.	
R33	Danger of cumulative effects.	
R37/38		
	Irritating to respiratory system and skin.	
R43	May cause sensitisation by skin contact.	
	(Contd. on	page 🤅
		5

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.01.2012

Vers.No.: 5

Revision: 03.01.2012

Trade name: SILIKAL RU 727

	(Contd. of page 8)
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic
	environment.

• **Department issuing MSDS:** Environmental Department • * **Data compared to the previous version altered.**