

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.01.2011

Vers.No.: 15

Revision: 31.01.2011

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** SILIKAL RE 77 Comp. A
- **Article number:** RE 77-A
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the preparation:**
Epoxy resin
Sealing
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Silikal GmbH
Ostring 23
D-63533 Mainhausen
Tel.: +49-6182/9235-0
Fax.: +49-6182/9235-40
e-mail: mail@silikal.de
- **Further information obtainable from:** Environmental department
- **Emergency telephone number:** +49 6182 / 9235-0

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
Xi; Irritant
R36/38: Irritating to eyes and skin.
Xi; Sensitising
R43: May cause sensitisation by skin contact.
N; Dangerous for the environment
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
- **Label elements**
- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**
  Xi Irritant
N Dangerous for the environment
- **Hazard-determining components of labelling:**
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)
- **Risk phrases:**
36/38 Irritating to eyes and skin.
43 May cause sensitisation by skin contact.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.01.2011

Vers.No.: 15

Revision: 31.01.2011

Trade name: SILIKAL RE 77 Comp. A

(Contd. of page 1)

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Safety phrases:

28 After contact with skin, wash immediately with plenty of soap and water.

37/39 Wear suitable gloves and eye/face protection.

61 Avoid release to the environment. Refer to special instructions/safety data sheets.

· Special labelling of certain preparations:

Contains epoxy constituents. See information supplied by the manufacturer.

· Other hazards**· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures**· Description:** Mixture of substances listed below with nonhazardous additions.**· Dangerous components:**

CAS: 25068-38-6 NLP: 500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)  Xi R36/38;  Xi R43;  N R51/53	50-100%
CAS: 9003-36-5	reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight = 700)  Xi R36/38;  Xi R43;  N R51/53	10-25%
CAS: 68609-97-2 EINECS: 271-846-8	oxirane, mono[(C12-14-alkyloxy)methyl] derivs  Xi R38;  Xi R43	2.5-10%

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· Description of first aid measures**· General information:** Immediately remove any clothing soiled by the product.**· After inhalation:** Supply fresh air and to be sure call for a doctor.**· After skin contact:** Immediately wash with water and soap and rinse thoroughly.**· After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

5 Firefighting measures

· Extinguishing media**· Suitable extinguishing agents:**

Water

Foam

Carbon dioxide

Fire-extinguishing powder

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· Advice for firefighters**· Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.01.2011

Vers.No.: 15

Revision: 31.01.2011

Trade name: SILIKAL RE 77 Comp. A

(Contd. of page 2)

· Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.
Cool endangered receptacles with water spray.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation
Wear protective clothing.
Use respiratory protective device against the effects of fumes/dust/aerosol.

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

· Handling:

· **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

· **Information about fire - and explosion protection:** No special measures required.

· **Conditions for safe storage, including any incompatibilities**

· Storage:

· **Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.
Store in cool, dry conditions in well sealed receptacles.
Do not allow to enter sewers/ surface or ground water.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Store receptacle in a well ventilated area.
Protect from heat and direct sunlight.

· **Maximum storage temperature:** 25°C

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **Additional information:** The lists valid during the making were used as basis.

· Exposure controls

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.01.2011

Vers.No.: 15

Revision: 31.01.2011

Trade name: SILIKAL RE 77 Comp. A

(Contd. of page 3)

Avoid contact with the eyes and skin.

Use skin protection cream for skin protection.

· **Respiratory protection:**

Use suitable respiratory protective device only when aerosol or mist is formed.

· **Protection of hands:**

Protective gloves

· **Material of gloves**

Butyl rubber, BR

Nitrile rubber, NBR

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:****Form:**

Fluid

Colour:

Yellow tint

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition****Melting point/Melting range:**

Undetermined.

Boiling point/Boiling range:

201°C

· **Flash point:**

140°C

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

> 200°C

· **Decomposition temperature:**

Not determined.

· **Self-igniting:**

Product is not selfigniting.

· **Danger of explosion:**

Product does not present an explosion hazard.

· **Explosion limits:****Lower:**

Not determined.

Upper:

Not determined.

· **Vapour pressure:**

Not determined.

· **Density at 20°C:**1.14 g/cm³· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **Evaporation rate**

Not determined.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.01.2011

Vers.No.: 15

Revision: 31.01.2011

Trade name: SILIKAL RE 77 Comp. A

(Contd. of page 4)

- | | |
|---|--|
| · Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| · Segregation coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic at 20°C: | 1400 mPas |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 0.0 % |
| Solids content: | 99.0 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
Keep away from heat and direct sunlight.
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Incompatible materials:** Reacts with alkali, amines and strong acids.
- **Hazardous decomposition products:** No dangerous decomposition products known.
- **Additional information:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**
- | | | |
|--|------|-------------------|
| · LD/LC50 values relevant for classification: | | |
| 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700) | | |
| Oral | LD50 | >5000 mg/kg (rat) |
| Dermal | LD50 | >2000 mg/kg (rat) |
- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Irritating effect.
 - **Sensitization:** Sensitization possible through skin contact.
 - **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological information

- **Toxicity**
 - **Acquatic toxicity:**
- | | |
|--|-------------------------|
| 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700) | |
| EC50 (48h) | 10 mg/l (Daphnia magna) |

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.01.2011

Vers.No.: 15

Revision: 31.01.2011

Trade name: SILIKAL RE 77 Comp. A

(Contd. of page 5)

LC50 (96h) 10 mg/l (fish)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
 Also poisonous for fish and plankton in water bodies.
 The material is harmful to the environment.
 Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 - **Recommendation**
 Must be specially treated adhering to official regulations.
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 - **European waste catalogue**
- | | |
|-----------|---|
| 07 02 08* | other still bottoms and reaction residues |
| 15 01 04 | metallic packaging |
- **Uncleaned packaging:**
 - **Recommendation:**
 Packaging may be reused or recycled after cleaning.
 Packagings that may not be cleansed are to be disposed of in the same manner as the product.
 - **Recommended cleansing agents:**
 Alcohol
 Acetone

14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 9 Miscellaneous dangerous substances and articles.
- **Danger code (Kemler):** 90
- **UN-Number:** 3082
- **Packing Group:** III
- **Hazard label** 9
- **Special marking:** Symbol (fish and tree)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.01.2011

Vers.No.: 15

Revision: 31.01.2011

Trade name: SILIKAL RE 77 Comp. A

(Contd. of page 6)

· **UN proper shipping name:** 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700))

· **Tunnel restriction code** E

· **Maritime transport IMDG:**



· **IMDG Class:** 9

· **UN Number:** 3082

· **Label** 9

· **Packaging group:** III

· **Marine pollutant:** No

· **Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700))

· **Air transport ICAO-TI and IATA-DGR:**



· **ICAO/IATA Class:** 9

· **UN/ID Number:** 3082

· **Label** 9

· **Special marking:** Symbol (fish and tree)

· **Packaging group:** III

· **Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700))

· **Special precautions for user** Warning: Miscellaneous dangerous substances and articles.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



Xi Irritant

N Dangerous for the environment

· **Hazard-determining components of labelling:**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

· **Risk phrases:**

36/38 Irritating to eyes and skin.

43 May cause sensitisation by skin contact.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.01.2011

Vers.No.: 15

Revision: 31.01.2011

Trade name: SILIKAL RE 77 Comp. A

(Contd. of page 7)

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Safety phrases:

28 After contact with skin, wash immediately with plenty of soap and water.

37/39 Wear suitable gloves and eye/face protection.

61 Avoid release to the environment. Refer to special instructions/safety data sheets.

· Special labelling of certain preparations:

Contains epoxy constituents. See information supplied by the manufacturer.

· National regulations:
· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Department issuing MSDS: Environmental Department

· * Data compared to the previous version altered.

GB